



CONSTRUCTIVE & DIMENSIONAL:

Application field:	Landscaped areas, Pathways, Driveways
Construction material:	Extruded aluminum EN AW-6060 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant waterrepellent lubricating solution
Length:	205mm(8,07")
Width:	80mm(3,14")
Height :	300mm(11,81")

ELECTRICAL FOR MODEL:

GH1462.NGFT300EN
GH1462.NGF.T

Description:	2 x 24 W LED 3000 K CRI>90 2938 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	2
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable H05RN-Fmm
Emergency kit:	Not available


OPTICAL:

Beam type:	Bollard 2 light
Beam angle [°]	180°
Light distribution:	Symmetric
Beam directionability:	Fixed
Diffuser material:	Soda-lime tempered glass 5mm
Diffuser finish:	Clear
Reflector material:	PMMA lens

LIGHTING SOURCE:

Light source:	LED
Power:	24 W
LED voltage range:	31.2-36.8V
Current:	350 mA
ZVEI - Led Type:	LED
Color temperature:	3000K for model
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2938 lm
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:

 .05 Dark grey (matt)	 .19 Light Grey
--	--

ACCESSORIES:



IP 68 connector
for through wiring
AC279



IP 68 fast
connector Small
AC204



Minitondo plated
steel anchorage
Compatto
AC274

