



GH1950.LFMT300EN
1950.HGM.T

H(m)	φ(m)	Lux Medi
5	0.9	822
4	0.7	1284
3	0.5	2283
2	0.4	5137
1	0.2	20547

GH1950.LFMT400EN
1950.HHM.T

H(m)	φ(m)	Lux Medi
5	0.9	834
4	0.7	1304
3	0.5	2318
2	0.4	5215
1	0.2	20858

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Facade, Columns, Walls, Covered entrances & walkways, Porch, balconies & terraces
Construction material:	Extruded aluminum EN AW-6063 T5 / die-casting alluminum EN-AB 44100
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Length:	273mm(10,74")
Width:	167mm(6,57")
Height:	590mm(23,22")

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1950.LFMT300EN 1950.HGM.T

Description:	1 x 26 W LED 3000 K CRI>90 2967 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	2
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Metal cable gland M16 Ø 5/10 mm
Emergency kit:	Not available
Light source:	LED
Power:	26W
LED voltage range:	31.2-36.8V
Current:	700 mA
ZVEI - Led Type:	COB
Color temperature:	3000 K
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	2967 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

ELECTRICAL and LIGHTING SOURCE for MODEL: GH1950.LFMT400EN 1950.HHM.T

Description:	1 x 26 W LED 4000 K CRI>90 3012 lm
Operating Power:	110-277 V / 50-60 Hz
Number of heads:	2
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Metal cable gland M16 Ø 5/10 mm
Emergency kit:	Not available
Light source:	LED
Power:	26W
LED voltage range:	31.2-36.8V
Current:	700 mA
ZVEI - Led Type:	COB
Color temperature:	4000 K
Binning:	Step MacAdam 3
Color rendering index:	CRI>90
Nominal LED emission:	3012 lm
Light source:	Included
Ambient temperature operating range:	- 20 °C ÷ +35 °C

NOTE*:

All this models are dimmable upon request:

OPTICAL:

Beam Type:	Wall-Effect 2 [21°-40°] medium
Beam angle:	28°
Light distribution:	Symmetric
Beam directionability:	Swivelling
Swivel [°]:	+/- 10°
Diffuser material:	Soda-lime tempered glass 10mm
Diffuser finish:	Clear
Reflector material:	Aluminium with super pure aluminum high vacuum deposit 99.5%
Reflector finish:	Aluminum

FINISH CODE:

.01 White (matt)
.45 Corten

.05 Dark grey (matt)
.80 Sand

.19 Light Grey