

DISKO OUTDOOR WALL

CONSTRUCTIVE & DIMENSIONAL:

Application field:	Porch, balconies & terraces, Walls
Construction material:	Anticorodal aluminum 6082, Extruded aluminum EN AW-6060 T5 high resistance to oxidation
External screws:	Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution
Diameter:	147mm(5,78")
Width:	28mm(1,10")
Height:	100mm(3,93")

ELECTRICAL FOR MODEL: GH1310.BRXO300EN

Description:	1 x 12 W LED 3000 K CRI>85 1300 lm
Operating Power:	110-277V / 50-60 Hz
Number of heads:	1
Number of circuits:	1
Driver positioning:	Integral
Control gear type:	Electronic
Cable entry:	Fixture supplied with pre-wired cable
Cord length:	0,5m

OPTICAL:

Beam type:	360° emission
Light distribution:	Light distribution diffused
Beam directionability:	Fixed
Diffuser material:	Polycarbonate
Diffuser finish:	Opal
Diffuser temperature:	< 50 °C / 126 °F

LIGHTING SOURCE:

Light source:	LED
Power:	12W
ZVEI - Led Type:	DOB
Color temperature:	3000K
Color rendering index:	CRI>85
Nominal LED emission:	1300 lm
Light source:	Included
Ambient temperature operating range:	-20 °C ÷ +35 °C

FINISH CODE:

.01 White (matt)	.05 Dark grey (matt)	.19 Light Grey
.26 Luxury Bronze	.45 Corten	.62 Antique Grey
.65 Blue	.80 Sand	

