



LED VERSIONS:

| H(m) | φ(m) | Lux Medi |
|------|------|----------|
| 5    | 54.9 | 0        |
| 4    | 43.9 | 0        |
| 3    | 33.0 | 1        |
| 2    | 22.0 | 2        |
| 1    | 11.0 | 7        |

### CONSTRUCTIVE & DIMENSIONAL:

|                        |   |
|------------------------|---|
| Application field:     | Porch, balconies & terraces, Passageways, Pathios, Covered entrances & walkways, Walkways and driveways |
| Construction material: | Die-cast aluminum EN AB 44100 highly resistant to oxidation   |
| External screws:       | Stainless steel A4-70 treated with highly antioxidant water-repellent lubricating solution              |
| Diameter:              | 270mm(10,62")   |

### ELECTRICAL and LIGHTING SOURCE for MODEL: GH0996.BRXO300EN 0996.147.O

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Description:                         | 1 x 13 W LED 3000 K CRI>85 2040 lm |
| Operating Power:                     | 110-277 V / 50-60 Hz               |
| Number of heads:                     | 1                                  |
| Driver positioning:                  | Integral                           |
| Control gear type:                   | Electronic                         |
| Emergency kit:                       | Not available                      |
| Light source:                        | LED                                |
| Power:                               | 13W                                |
| ZVEI - Led Type:                     | DOB                                |
| Color temperature:                   | 3000 K                             |
| Color rendering index:               | CRI>85                             |
| Nominal LED emission:                | 2040 lm                            |
| Light source:                        | Included                           |
| Ambient temperature operating range: | -20 °C ÷ +35 °C                    |

### ELECTRICAL and LIGHTING SOURCE for MODEL: GH0996.BRXO400EN 0996.148.O

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Description:                         | 1 x 13 W LED 4000 K CRI>85 2140 lm |
| Operating Power:                     | 110-277 V / 50-60 Hz               |
| Number of heads:                     | 1                                  |
| Driver positioning:                  | Integral                           |
| Control gear type:                   | Electronic                         |
| Emergency kit:                       | Not available                      |
| Light source:                        | LED                                |
| Power:                               | 13W                                |
| ZVEI - Led Type:                     | DOB                                |
| Color temperature:                   | 4000 K                             |
| Color rendering index:               | CRI>85                             |
| Nominal LED emission:                | 2140 lm                            |
| Light source:                        | Included                           |
| Ambient temperature operating range: | -20 °C ÷ +35 °C                    |

### ELECTRICAL and LIGHTING SOURCE for MODEL: GH0996.36XOXXXEX 0996.36F.O

|                                      |                      |
|--------------------------------------|----------------------|
| Description:                         | 1 x 57 W             |
| Operating Power:                     | 110-277 V / 50-60 Hz |
| Number of heads:                     | 1                    |
| Emergency kit:                       | Not available        |
| Lampholder:                          | E26                  |
| Power:                               | 57W                  |
| ZVEI - Led Type:                     | INC                  |
| Light source:                        | Not Included         |
| Ambient temperature operating range: | -20 °C ÷ +35 °C      |

### OPTICAL:

|                        |   |
|------------------------|---|
| Beam Type:             | Wall extrawide                          |
| Light distribution:    | Assymmetric                             |
| Beam directionability: | Fixed                                   |
| Diffuser material:     | Vandal proof polycarbonate UV resistant |
| Diffuser finish:       | Opal                                    |

### FINISH CODE:

|                      |                |                  |
|----------------------|----------------|------------------|
| .05 Dark grey (matt) | .19 Light Grey | .01 White (matt) |
| .02 Black (matt)     | .45 Corten     | .80 Sand         |